



**5.0 Melt**  
Eco-Friendly  
Product

BLACK COMMODITY is a high quality recycled resin sourced exclusively from rotomolding. It helps reduce plastic waste with great mechanical properties and aesthetics.



**Find More  
Information**



[www.rotopolymers.com](http://www.rotopolymers.com)  
**+ 1 216 591 0175**  
[info@rotopolymers.com](mailto:info@rotopolymers.com)

# COMMODITY

## METHOD<sup>2</sup>

## VALUE

DENSITY	D1505 Reference MA-01 Own Method	0.935 g/cm <sup>3</sup>
MELT INDEX @190°C/2.16 kg	ASTM D1238	5.0 g/10 min
TENSILE STRENGTH AT YIELD <sup>1</sup> @ 50mm/min	ASTM D638	1,947 psi (13.4 MPa)
LOW TEMPERATURE IMPACT @ -40°C <sup>1</sup>	ARM 1/8" specimen	51.7 ft/lb (69.8 J)
ELONGATION AT BREAK <sup>1</sup>	ASTM D638	253 %
PROCESSING WINDOW	Rotomolding	180 - 195 °C



UV8  
Stabilized



RECYCLED  
Product



SMOOTH  
Black

- <sup>1</sup> Rotational Molded
- <sup>2</sup> Test methods may be modified to accommodate conditions or laboratory limitations
- <sup>3</sup> Test equipment upper limit for elongation is 600%

The following are typical properties and are not to be construed as specifications.

Tests were done on natural, unpigmented resin.

User is advised to make its own determination of this product's suitability for its intended use.

Roto Polymers makes no warranty expressed or implied regarding the suitability of this product in application.

[www.rotopolymers.com](http://www.rotopolymers.com)

+ 1 216 591 0175

[info@rotopolymers.com](mailto:info@rotopolymers.com)